

2019 GRAND TOURING LIMITED NEW

PACKAGE HIGHLIGHTS

- Rotax® 600R E-TEC®, 900 ACE™ Turbo and 900 ACE™ engines
- RAS™ 3 front suspension
- REV™ Gen4 platform with wide-design bodywork
- pDrive™ clutch
- Heated 2-up seat with heated passenger handholds and air deflectors
- SilentDrive™ system with 15 x 137 x 1.25 in. Silent Track II
- rMotion™ with Air Control Suspension (ACS)
- Heated visor outlets for driver and passenger
- Brembo brake with braided stainless-steel brake line
- RER™ electronic reverse (600R E-TEC®) / Electro-mechanic reverse (ACE™ engines)
- Multifunction digital gauge with display
- Ergo-Step side panels
- RF D.E.S.S.™ key
- Warm glove box with 4 L / 1 US gal of storage
- Forward Adjustable Riser
- Large rear LinQ cargo box with 62 L / 16.1 US gal of storage
- Heavy duty rear bumper
- Premium protection: 26.5-in. Ultra-high windshield, side panels wind deflectors, rear snow deflector and running boards with small openings
- Heated boot plug
- Pivoting mirrors

EXTRA HIGHLIGHTS

- ACE™ engines**
- 900 ACE™ engine with 650W magneto
 - 900 ACE™ Turbo engine with 650W magneto and air radiator with fan
 - iTC™ Engine mapping modes (Standard, Sport or ECO®)
 - Engine oil cooler



GRAND TOURING LIMITED 900 ACE™ TURBO shown

ROTAX® ENGINE

	600R E-TEC®	900 ACE™ TURBO	900 ACE™
Engine details	Liquid-cooled, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	3	3
Displacement	599.4 cc / 36.6 in. ³	899 cc / 54.9 in. ³	899 cc / 54.9 in. ³
Bore	72.3 mm / 2.85 in.	74 mm / 2.9 in.	74 mm / 2.9 in.
Stroke	73 mm / 2.87 in.	69.7 mm / 2.7 in.	69.7 mm / 2.7 in.
Maximum engine speed	8,100 RPM	7,250 RPM	7,250 RPM
Carburation	E-TEC direct injection	EFI	EFI
Recommended fuel type	Premium unleaded	Premium unleaded	Regular unleaded
Minimum octane	91	91	87
Fuel tank	36 L / 9.5 US gal	36 L / 9.5 US gal	36 L / 9.5 US gal
Oil tank capacity	3.4 L / 3.6 qt	3.3 L / 3.5 qt	3.3 L / 3.5 qt

POWERTRAIN

	pDrive™	pDrive™	pDrive™ with slider shoes
Drive clutch type	QRS	QRS	QRS
Driven clutch type	3,400 RPM	2,200 RPM	2,200 RPM
Engagement	23	25	24
Small sprocket number of teeth	45	45	49
Large sprocket number of teeth	16	16	16
Drive sprocket number of teeth	177 mm / 7 in.	177 mm / 7 in.	177 mm / 7 in.
Drive sprocket diameter	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line
Brake system			

DRY WEIGHT

261 kg / 575 lb	282 kg / 621 lb	269 kg / 594 lb
-----------------	-----------------	-----------------

FEATURES

Frame	REV® Gen4	Riser block height	Adjustable-120 mm / 4.7 in.	Mirrors	Standard
Bodywork	Wide design	Starter	Electric	Windshield	771 mm / 28 in.
Skis	Pilot™ 5.7 SL	Reverse	RER™ (600R E-TEC®) Electro-mechanic (ACE™ engines)	Runner	Round 1/2
Seating	2-up heated	Heated throttle lever/ grips	Standard (driver and passenger)	Carbide configuration	102 mm / 4 in. at 90°
Handlebar	U-shaped aluminum	Gauge	Multifunction	Hitch	Optional

ALL ENGINES

GRAND TOURING LIMITED



GRAND TOURING LIMITED 900 ACE™ shown



GRAND TOURING LIMITED 900 ACE™ TURBO shown

FEATURE HIGHLIGHTS



Comfort and luxury

Driver and passenger are surrounded by little things that make epic trips easier and more comfortable. Such as: Ultra-high windshield, heated visor outlets, electric start, push-button reverse, mirrors and more.



Large cargo box

Hard-top weather-resistant LinQ box adds 62 L (16.1 US gal) of storage on the tunnel.



Air Control Suspension (ACS)

Tailors the ride for load or trail conditions via a rear air spring and an onboard compressor. Five preload settings are selectable on-the-fly via a handlebar rocker switch.



2-up heated seat with passenger handholds

Premium 2-up heated seat with backrest, including handholds.



Multifunction gauge with LCD screen

GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	Standard

ski-doo

